



QUASAR S130

Flat, round safety luminaire for ceiling mounting made of white polycarbonate. To reduce maintenance costs, the luminaire is equipped with a screwless locking mechanism. In addition, all the recesses in the luminaire can be replaced without tools.


Available with optics for wide area or escape route illumination or with hall downlight for high ceilings heights.

The luminaire is equipped with a 3 W power LED (switching type: non-maintained mode).




Technical specifications


Connecting terminals	2 x 2.5 mm ² for double assignment
Casing/colour	Polycarbonate / white
Type of assembly	Ceiling mounting
Dimensions (Ø x H)	131 x 38 mm
Protection class	IP40
Safety class	II




Wide Area Optic



Escape Route Optic



Cable entry guide




Self contained luminaires

Technical specifications

Voltage supply	230V 50/60Hz
NiMH battery	4,8V 2,0Ah
Luminous flux	100% / 20% emergency / mains (1h + 3h) 50% / 20% emergency / mains (8h)

Temperature range BS 0°C to +35°C
Temperature range DS -5°C to +30°C



Order information

Item number	Description	Illuminant	Light current mains operation	Light current emergency	Power consumption	Rated operating time
LE406402-SL	QUASAR S 130-PC A-F EB-SL LED	3W LED	120lm	280lm	5VA	1h
LE406402-SWX	QUASAR S 130-PC A-F EB-SWX LED	3W LED	120lm	280lm	5,5VA	1h
LE406412-SL	QUASAR S 130-PC A-R EB-SL LED	3W LED	120lm	280lm	5VA	1h
LE406412-SWX	QUASAR S 130-PC A-R EB-SWX LED	3W LED	120lm	280lm	5,5VA	1h

Self contained luminaires

SC	Self monitoring SELF CHECK
SL	Bus control SAFELOG Line
SW	Wireless monitoring SAFELOG

General

F	Wide area optic
R	Escape route optic
T	Downlight optic

Our standard casing colours

White	RAL 9016
Black	RAL 9005